

GIPIEMME made in italy -		www.gpiemme.com		wheel model			
08-06-2012				Modello Ruota			
wheel technical specifications:				KENYA 27.5" ULTRALIGHT 32 RAGGI			
Scheda Tecnica Ruota modello:				TUBELESS			
				etrto -584-17 din old135			
SIZES	MISURE	Tyre	COPERTURA	1	Clincher / Tubeless	Copertoncino / Tubeless	
		Size	MISURA	2	27.5" - mtb		
		Etrto	ETRTO	3	ETRTO 584- 17 DIN		
REAR Wheel - RIGHT side	POSTERIORE LATO DX	Spokes No.	Q.TA' RAGGI	4	16		
		Spokes Length	LUNGH. RAGGI	5	L 276		
		Spokes Crossing	TIPO INCROCIO	6	Cross x 3 (Inner/Outer overlapping)	Inc. x 3 (Inf./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	7	125 ± 8%		
REAR Wheel - LEFT side	POSTERIORE LATO SX	Spokes No.	Q.TA' RAGGI	8	16		
		Spokes Length	LUNGH. RAGGI	9	L 278		
		Spokes Crossing	TIPO INCROCIO	10	Cross x 3 (Inner/Outer overlapping)	Inc. x 3 (Inf./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	11	85 ± 8%		
FRONT Wheel - RIGHT side	ANTERIORE LATO DX	Spokes No.	Q.TA' RAGGI	12	16		
		Spokes Length	LUNGH. RAGGI	13	L 280		
		Spokes Crossing	TIPO INCROCIO	14	Cross x 3 (Inner/Outer overlapping)	Inc. x 3 (Inf./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	15	100 ± 8%		
FRONT Wheel - LEFT side	ANTERIORE LATO SX	Spokes No.	Q.TA' RAGGI	16	16		
		Spokes Length	LUNGH. RAGGI	17	L 276		
		Spokes Crossing	TIPO INCROCIO	18	Cross x 3 (Inner/Outer overlapping)	Inc. x 3 (Inf./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	19	100 ± 8%		
Spokes & Nipples Specifications	SPECIFICHE RAGGI NIPLES ALTRO	Spokes Type	TIPO RAGGI INOX	20	SAPIM LASER Ø2 with reduced section	SAPIM LASER Ø2 con sezione ridotta	
		Spokes Colour	COLORE RAGGI	21	black	nero	
		Nipples Type	TIPO NIPLES	22	ACI ABS ERGAL L15 T.E.		
		Nipples Material	MATERIALE-COLORE Nipples	23	Ergal RED		
		Washer	PIASTRINA/ROSETTA	24	RONDELLE OTTONE		
		Cross spokes	INCROCIO RAGGI	25	////////	////////	
		Nipples Stopper	FRENA FILETTI	26	NO (autolock Nipples)		
RIMS Specifications	SPECIFICHE CERCHIO	Rim Material	MATERIALE	27	AL 6082 T6		
		Rim Sizes	TIPO PROFILO	28	H 20 X 23 Welded (Saldato) DIAM. 597 - ETRTO 584		
		Rim Colour	COLORE CERCHIO	29	Anodiz. Black	Anodiz. Nero	
		Ø Valve Hole	Ø FORO VALVOLA	30	Ø 6,5 inner//outer	Ø 6,5 interno//esterno	
		Eyelets	BOCCOLE	31	yes	si	
		Decoration	DECORAZIONI	32	Laser + Sticker	Laser + Etichette	
		HUBS Specifications	SPECIFICHE MOZZO E CUSCINETTI	Front Hub	MOZZO ANT.	33	LIGHT DISC FC-H-1
Rear Hub SH.	MOZZO POST. SH.			34	LIGHT DISC RC-H-1		
O.L.D. Front/Rear Axle	INTERASSE BATTUTA			36	100/135 mm.		
Spokes Holes Front/rear	FORI POST./ANT.			37	32/32 (std)		
Hub Colour	COLORE MOZZO			38	BLACK	NERO	
Front Hub Motion	CUSCINETTI 2RS ANT.			39	N.2 Ø 10 / 26 x 8		
Rear Hub Motion	CUSCINETTI 2RS POST.			40	N. 2 Ø 15 / 28 x 7		
SHIMANO cassette body	CASSETTE SHIMANO-CUSCINETTI-GHIERE			Material	MATERIALE	41	Ergal anodized
		Shimano	SHIMANO	42	8/9/10S 12/11 teeth	8/9/10S 12/11 denti	
		Cassette Motion	CUSCINETTI 2RS	43	N.2 Ø15/28X7		
		Cog - 12	GHIERA 12 DENTI	44	std Shimano		
		Cog - 11	GHIERA 11 DENTI	45	std Shimano		
		Thightness Torque in Nm	SERRAGGIO GHIERA	46	35/45 Nm		
Quick Release	BLOCCAGGI	O.L.D.	INTERASSE CHIUSURA	56	100/135		
		Colour	COLORE	57	Black		
		Model	MODELLO	58	Light MtB k		
		Weight	PESO	59	gr. 114		
WHEELS WEIGHT	PESO RUOTE	Front Wheel	RUOTA ANT. Gr.	60	727		
		Rear Wheel	RUOTA POST. GR.	61	868		
		Wheel SET ± 5%	COPPIA RUOTE GR. ± 5%	62	1595		
ASSEMBLYING TOLLERANCE FRONT & REAR	TOLLERANZE RUOTE Anteriore &	Max Roundness	Salto Max	63	0,30 mm.		
		Max obbling	Sbandamento Max	64	0,30 mm.		
		Max Symmetry	Campanatura Max	65	0,50 mm.		