

wheel technical specifications:

Scheda Tecnica Ruota modello:

PISTA 030FIXED colori vari

TRACK 28"-700C cop. Old120/100

			#				
Sizes	MISURE	Tyre	COPERTURA	1	Clincher	Copertoncino	
		Size	MISURA	2	28" - 700C		
		Etrto	ETRTO	3	ETRTO 622 - 13.5 DIN		
REAR Wheel - RIGHT side	POSTERIORE LATO DX	Spokes No.	Q.TA' RAGGI	4	16		
		Spokes Lenght	LUNGH. RAGGI	5	285		
		Spokes Crossing	TIPO INCROCIO	6	Cross x 3 (Inner/Outer overlapping)	Inc. x 3 (Int./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	7	130 ± 8%		
REAR Wheel - LEFT side	POSTERIORE LATO SX	Spokes No.	Q.TA' RAGGI	8	16		
		Spokes Lenght	LUNGH. RAGGI	9	285		
		Spokes Crossing	TIPO INCROCIO	10	Cross x 3 (Inner/Outer overlapping)	Inc. x 3 (Int./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	11	130 ± 8%		
FRONT Wheel - RIGHT side	ANTERIORE LATO DX	Spokes No.	Q.TA' RAGGI	12	16		
		Spokes Lenght	LUNGH. RAGGI	13	285		
		Spokes Crossing	TIPO INCROCIO	14	Cross x 3 (Inner/Outer overlapping)	Inc. x 3 (Int./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	15	130 ± 8%		
FRONT Wheel - LEFT side	ANTERIORE LATO SX	Spokes No.	Q.TA' RAGGI	16	16		
		Spokes Lenght	LUNGH. RAGGI	17	285		
		Spokes Crossing	TIPO INCROCIO	18	Cross x 3 (Inner/Outer overlapping)	Inc. x 3 (Int./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	19	130 ± 8%		
Spokes & Nipples Specifications	SPECIFICHE RAGGI NIPLES ALTR0	Spokes Type	TIPO RAGGI	20	ROUND Ø 2 ucp	TONDO Ø 2 ucp	
		Spokes Colour	COLORE RAGGI	21	nero / black		
		Nipples Type	TIPO NIPLES	22	zincato		
		Nipples Material	MATERIALE-COLORE Nipples	23	acciaio zincato		
		Washer	PIASTRINA/ROSETTA	24	no	no	
		Nipples Stopper	FRENA FILETTI	25	NO (autolock Nipples)		
RIMS Specifications	SPECIFICHE CERCHIO	Rim Material	MATERIALE	26	AL 6005 T6		
		Rim Sizes	TIPO PROFILO	27	H 30 X 19 / 13.5		
		Rim Colour	COLORE CERCHIO	28	Paint black / white	verniciato nero / bianco	
		Ø Valve Hole	Ø FORO VALVOLA	29	Ø 6.5 / 8.5		
		Rubber hole valve	GOMMINO FORO VQALVOLA	30	no	no	
		Eyelets	BOCCOLE	31	no	no	
		Decoration	DECORAZIONI	32	Sticker 2 X edge	Etichette 2 per lato	
HUBS Specifications	SPECIFICHE MOZZO E CUSCINETTI	Front Hub	MOZZO ANT.	33	PISTA FRONT sfere -32H		
		Rear Hub SH.	MOZZO POST. SH.	34	PISTA REAR sfere -32H flip-flap		
		O.L.D. Front/Rear Axle	INTERASSE BATTUTA	36	100/120 mm.		
		Spokes Holes Front/rear	FORI POST./ANT.	37	32/32		
		Hub Colour	COLORE MOZZO	38	SILVER / NERO BLACK		
		Front Hub Motion	CUSCINETTI 2RS ANT.	39	N.2		
		Rear Hub Motion	CUSCINETTI 2RS POST.	40	N.2		
WHEELS WEIGHT	PESO RUOTE	Front Wheel	RUOTA ANT. Gr.	60	1159		
		Rear Wheel	RUOTA POST. GR.	61	1230		
		Wheel SET ± 5%	COPIA RUOTE GR. ± 5%	62	2389		
ASSEMBLYING TOLLERANCE FRONT &	TOLLERANZE RUOTE Anteriore &	Max Roundness	Salto Max	63	0,30 mm.		
		Max obbling	Sbandamento Max	64	0,30 mm.		
		Max Simmetry	Campanatura Max	65	0,50 mm.		
Reccomended assembly	RACCOMANDA ZIONI D'USO	Reccomended Tyre	COPERTURA SUGGERITA	72	19 ÷ 25		
		Rim tape - Flap	NASTRO - FLAP	73	622 x 16 x 0,6		
		Max Inflate (Bars)	MAX PRES. CONSENTITA	74	Tyre/Copert. 19 ► 10 Bar - Tyre/Copert. 25 ► 9 Bar		
		Braking pads	PATTINI FRENO	75	standard		