

G I P I E M M E made in italy -		www.gipiemme.com		wheel model	
07-12-2011				Modello Ruota	
wheel technical specifications: Schema Tecnica Ruota modello:				#	KENYA Tubular disc CX 29" -632 old135
Sizes	MISURE	Tyre	COPERTURA	1	Tubular Tubolare
		Size	MISURA	2	29" - mtb
		Etrto	ETRTO	3	ETRTO 632- 25 DIN
REAR Wheel - RIGHT side	POSTERIORE LATO DX	Spokes No.	Q.TA' RAGGI	4	16
		Spokes Lenght	LUNGH. RAGGI	5	L 292
		Spokes Crossing	TIPO INCROCIO	6	Cross x 3 (Inner/Outer overlapping) Inc. x 3 (Int./Est. a contatto)
		Spokes Tension Kg.	TENSIONE IN KG.	7	125 ± 8%
REAR Wheel - LEFT side	POSTERIORE LATO SX	Spokes No.	Q.TA' RAGGI	8	16
		Spokes Lenght	LUNGH. RAGGI	9	L 294
		Spokes Crossing	TIPO INCROCIO	10	Cross x 3 (Inner/Outer overlapping) Inc. x 3 (Int./Est. a contatto)
		Spokes Tension Kg.	TENSIONE IN KG.	11	85 ± 8%
FRONT Wheel - RIGHT side	ANTERIORE LATO DX	Spokes No.	Q.TA' RAGGI	12	16
		Spokes Lenght	LUNGH. RAGGI	13	L 298
		Spokes Crossing	TIPO INCROCIO	14	Cross x 3 (Inner/Outer overlapping) Inc. x 3 (Int./Est. a contatto)
		Spokes Tension Kg.	TENSIONE IN KG.	15	100 ± 8%
FRONT Wheel - LEFT side	ANTERIORE LATO SX	Spokes No.	Q.TA' RAGGI	16	16
		Spokes Lenght	LUNGH. RAGGI	17	L 294
		Spokes Crossing	TIPO INCROCIO	18	Cross x 3 (Inner/Outer overlapping) Inc. x 3 (Int./Est. a contatto)
		Spokes Tension Kg.	TENSIONE IN KG.	19	100 ± 8%
Spokes & Nipples Specifications	SPECIFICHE RAGGI NIPLES ALTRO	Spokes Type	TIPO RAGGI INOX	20	Aerodynamic Ø 2 with reduced section aerodinamico Ø 2 con sezione ridotta
		Spokes Colour	COLORE RAGGI	21	black nero
		Nipples Type	TIPO NIPLES	22	ACI ABS ERGAL L15 T.E.
		Nipples Material	MATERIALE-COLORE Nipples	23	Ergal RED
		Washer	PIASTRINA/ROSETTA	24	NO
		Cross spokes	INCROCIO RAGGI	25	rubber isolation gommino isolante
RIMS Specifications	SPECIFICHE CERCHIO	Nipples Stopper	FRENA FILETTI	26	NO (autolock Nipples)
		Rim Material	MATERIALE	27	AL 6082 T6
		Rim Sizes	TIPO PROFILO	28	H 20 X25 Welded (Saldato)
		Rim Colour	COLORE CERCHIO	29	Anodiz. Black Anodiz. Nero
		Ø Valve Hole	Ø FORO VALVOLA	30	Ø 6,5 inner//outer Ø 6,5 interno//esterno
		Eyelets	BOCCOLE	31	yes si
HUBS Specifications	SPECIFICHE MOZZO E CUSCINETTI	Decoration	DECORAZIONI	32	Laser + Sticker Laser + Etichette
		Front Hub	MOZZO ANT.	33	LIGHT DISC FC-H-1
		Rear Hub SH.	MOZZO POST. SH.	34	LIGHT DISC RC-H-1
		Q.L.D. Front/Rear Axle	INTERASSE BATTUTA	36	100/135 mm.
		Spokes Holes Front/rear	FORI POST./ANT.	37	32/32 (std)
		Hub Colour	COLORE MOZZO	38	BLACK NERO
SHIMANO cassette body	CASSETTE SHIMANO- CUSCINETTI- GHIERE	Front Hub Motion	CUSCINETTI 2RS ANT.	39	N.2 Ø 10 / 26 x 8
		Rear Hub Motion	CUSCINETTI 2RS POST.	40	N. 2 Ø 15 / 28 x 7
		Material	MATERIALE	41	Ergal anodized Ergal anodizzato
		Shimano	SHIMANO	42	8/9/10S 12/11 teeth 8/9/10S 12/11 denti
		Cassette Motion	CUSCINETTI 2RS	43	N.2 Ø15/28X7
		Cog - 12	GHIERA 12 DENTI	44	std Shimano
Quick Release	BLOCCAGGI	Cog - 11	GHIERA 11 DENTI	45	std Shimano
		Tightness Torque in Nm	SERRAGGIO GHIERA	46	35/45 Nm
		Q.L.D.	INTERASSE CHIUSURA	56	100/135
		Colour	COLORE	57	Black
WHEELS WEIGHT	PESO RUOTE	Model	MODELLO	58	Light Mtb k
		Weight	PESO	59	gr. 114
		Front Wheel	RUOTA ANT. Gr.	60	74.7
ASSEMBLYING TOLLERANCE FRONT & REAR	TOLLERANZE RUOTE Anteriore &	Rear Wheel	RUOTA POST. GR.	61	888
		Wheel SET ± 5%	COPPIA RUOTE GR. ± 5%	62	1635
		Max Roundness	Salto Max	63	0,30 mm.
		Max obbling	Sbandamento Max	64	0,30 mm.
		Max Simmetry	Campanatura Max	65	0,50 mm.